

# PRO 120 SERIES

This LED ribbon is great for accent applications such as coves, shelving and toe-kicks, which can be installed in both dry and wet locations.



PRODUCT CODE	LUMENS/FT	EFFICACY
NF-PRO-O-120-[12V/24V]-2700K	214	71
NF-PRO-O-120-[12V/24V]-3000K	210	70
NF-PRO-O-120-[12V/24V]-3225K	197	66
NF-PRO-O-120-[12V/24V]-4100K	212	71
NF/SP-PRO-O-120-[12V/24V]-5500K	208	69
NF-PRO-O-120-[12V/24V]-6200K	177	59

Also available in IP22 and IP68



## PHYSICAL

Operating Temp	-15° F to +140° F (-26° C to +60° C)
Class II Max Run	16 ft (12V) / 32 ft (24 V)
CRI	80+
Cut Length	1 in (12V) / 2 in (24V)
Environment	IP65
Mounting	3M Adhesive / Clips / Channels
Width	0.40 in (10.16 mm)
Height	0.14 in (3.56 mm)



## ELECTRICAL

Input Voltage	12V / 24V DC
Power Consumption	3.0 w/ft
LEDs/Meter	120
Lamp Life	50,000+ hours
Wire Size	20 AWG, 2 wire
Dimming	MLV / ELV / 0-10V
Certifications	UL Listed
Warranty	2 years

