

MINI NEON SERIES

NOVA FLEX®

The Mini Neon Series offers architectural-grade LED neon with a tighter radius to allow more flexibility.

- UV, Chemical & Saltwater Resistant
- Single Bin Only: 3 Step MacAdam
- UL Certified



INSPECTION READY ✓

Physical

Operating Temp	-15° to 140°F (-25° to 60°C)
Environment	IP68 Rugged (Water/chemical resistant)
Mounting	Clips Channel (Required)
Cut Marks	See diagram below
Lead Options	Right, Bottom, Left and Back
Bend Radius	3.54 in

Performance

Lumen Maintenance	50,000 Hrs
Warranty	3 years
CCT Binning	<3SDCM
Certifications	UL Wildlife Lighting, Turtle Friendly (IP68, Red & Yellow)

Electrical

Voltage	24V
Wire Size	18 AWG. 2 Wire
Dimming	MLV 0-10V S3i Series Controller

Dimensions



ORDER CODE	SERIES	ENV	MINI	VOLTAGE	CCT
NF	NEON	W	MINI	24V	
NF	NEON	W = IP68	MINI	24V	2700K 3000K 3500K 5500K RED GREEN BLUE YELLOW*

	CCT	Lumens/ft	Efficacy (lm/w)	Power (w/ft)	Max Run
Mini Neon	2700K	27	19	1.4	49.2 ft
	3000K	27	19		
	3500K	30	22		
	5000K	30	22	1.0	
	Red	13	12		
	Green	24	22	1.4	
	Blue	5	4		
	Yellow*	15	14		


Lumens have a tolerance of +/- 10%.

Complete Solution

- Step 1 Build your ribbon order code
- Step 2 Select your channel (pg 2)
- Step 3 Select your power and controls (pg 3-4)
- Step 4 Select your accessories (pg 5)
- Step 5 Contact your local agent or Nova Flex Rep.



Lead Options Available: Right Side, Left Side, Back Side and Bottom Side Lead.




DID YOU KNOW?
Product is cut, soldered & shipped ready to install in 1 - 4 business days.

IES | LM79 | INSTALL GUIDE

*Special order, allow 4 - 6 weeks delivery.

MINI NEON CHANNEL & CLIPS

NOVA FLEX[®]



Physical

Material	Anodized Aluminum
Length	Custom Length up to 6.56 ft (2M)
Color	Silver



Mounting Options




Direct Mount

POWER SUPPLY OPTIONS MINI NEON SERIES

Dimming Options: No control needed

Product Image	Product Code	Wattage	Output Current	Input Voltage	Safety	Downloads
E-SERIES MLV DIMMABLE DOWN TO 1%						
	NF-PS-E20L24	20W	0.87A	120 VAC	UL8750 Class 2 Nema 3R	20W SPECS
	NF-PS-E40L24	40W	1.75A			40W SPECS
	NF-PS-E60L24	60W	2.63A			60W SPECS
	NF-PS-E75L24	75W	3.30A			75W SPECS
	NF-PS-E96L24	96W	4.00A			96W SPECS
	NF-PSEZJ192L24	2 X 96W	2.67A	120 VAC	UL Approved Class 2	EZJ 192 SPECS
	NF-PSEZJ288L24	3 x 96W	4.00A			EZJ 288 SPECS

ELECTRONIC 0-10V DIMMABLE DOWN TO 0.1%

	NF-PS-96W-24V-0/10V	96W	0.96A Max	120-277 VAC	UL8750 Class 2 Class P	SPEC SHEET
---	---------------------	-----	-----------	-------------	------------------------	----------------------------

Non-Dimming Options: Can be paired with a control on the next page.

ELECTRONIC NON-DIMMING (unless paired with a dimmable controller)











	NF-PS-35W-24V-HW	35W	Input 1.1A Max Output 1.5A / 24V	100 - 240 VAC	UL E345214 Class 2	SPEC SHEET
	NF-PS-60W-24V-HW	60W	Input 1.2A Max Output 2.5A / 24V	100 - 240 VAC	UL E345214 Class 2	SPEC SHEET
	NF-PS-96W-24V	96W	Input 0.96A Max Output 4.1A / 24V	120 - 277 VAC	UL E345214 Class 2	SPEC SHEET
	NF-PS-HLG100W24V-HW	100W	Input 1.2A Max Output 4.0A / 24V	100 - 277 VAC	UL E345214 Class 2	SPEC SHEET

PLUG & PLAY









	NF-PS-12W-24V-WM	12W	0.25A Max	100 - 240 VAC	UL E345214 Class 2	12W SPECS
	NF-PS-24W-24V-WM	24W	0.5A Max			24W SPECS
	NF-PS-36W-24V-TT	36W	0.9A Max	100 - 240 VAC	UL E345214 Class 2	36W SPECS
	NF-PS-60W-24-TT	60W	1.5A Max			60W SPECS
	NF-PS-100W-24V-TT	100W	4.0A Max			100W SPECS

CONTROL OPTIONS MINI NEON SERIES

If you have a large project, these controls can be paired with our Universal Amplifier.

Product Image	Product Code	Details	Pair With	Downloads
S3i CONTROL SERIES				
	S3i Rotary Wall Mount NF-S3i-RC-D	Zones: 1 Power Consumption: 200ma Dimming Function: 0 - 100% Battery Operated: Included	NF-S3i-WR-1009	SPEC SHEET
	S3i Touch Static Dimmer NF-S3i-TP-D	Zones: 4 Power Consumption: 200ma Dimming Function: 0 - 100%	NF-S3i-WR-1009	SPEC SHEET
	S3i Hand-held Static Dimmer NF-S3i-WC-D	Zones: 6 Dimming Function: 0 - 100% Battery Operated: 3 AAA	NF-S3i-WR-1009	SPEC SHEET
	S3i Push Button Wall Mount Static Dimmer NF-S3i-PB-D	Zones: 1 Dimming Function: 0 - 100% Battery Operated: 3V (CR2025)	NF-S3i-WR-1009	SPEC SHEET
	S3i WiFi RF Converter NF-S3i-WC-WIFI	Output Power: RF Signal Operating Frequency: 2.4G Dimming: 0 - 100%	NF-S3i-WR-1009	SPEC SHEET
	S3i Wireless Receiver NF-S3i-WR-1009	Output Power: 240 - 720w Output Current: 4 CH. 5A/CH Input: 12 - 36V DC Dimming: 0 - 100%	NF-A-UNV	SPEC SHEET
OTHER CONTROLS AND AMPLIFIER				
	LT Static Dimmer NF-WC-D	Zones: 1 Receiver Voltage: 12 - 24V DC Receiver Power Capacity: 126W (24V) Remote Voltage: 3V (CR2025) Remote Working Frequency: 433.92 MHz	NF-A-UNV	SPEC SHEET
	LED DMX Decoder NF/SP-DMX-5A-4CH	Input Voltage: 12 - 24V DC Max Output Power: 480W Max Load Current: 20A (5A/4CH) Short Circuit / Over Load Recover Automatically Control Method: DMX512 RJ45	Electronic Non-Dimming Driver	SPEC SHEET
	0-10V - 12/24V Dimming Module NF-D-0/1-10V	Input Signal: 0-10V, 1-10V, 10V PWM, Push Button Input Voltage: 12 - 24V DC Max Load Current: 1 CH (10A/CH) Max Output Power: 120W/288W (12V/24V) Dimming Range: 0 - 100%	Electronic Non-Dimming Driver	SPEC SHEET
	Universal Amplifier NF-A-UNV	Input Voltage: 12 - 36V DC Input Signal: PWM Max Load Current: 20A (5A/4CH) Max Output Power: 240 - 720W	All Above Products	SPEC SHEET

ACCESSORY OPTIONS MINI NEON SERIES

Product Image	Product Code	Dimensions
	Hardwire to Female Quick Connect Adapter NF-C-F	Available Lengths: 6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 8ft & 10ft
	Y Cable 2 Male, 1 Female NF-C-Y	Total Length: 20.00 in
	Hardwire to Male Quick Connect Adapter NF-C-M	Available Lengths: 6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 8ft & 10ft
	Y Cable 4 Male, 1 Female NF-C-Y-4Y	Total Length: 20.00 in
	Male to Female Quick Connect Extension NF-C-MF	Available Lengths: 3ft, 6ft & 10ft
	Y Cable 8 Male, 1 Female NF-C-Y-8Y	Total Length: 17.25 in
	Female Quick Connect to Hardwire Adapter NF-C-F/HW	1.5 x 0.5 x 0.5 in
	Male Quick Connect to Hardwire Adapter NF-C-M/HW	1.5 x 0.5 x 0.5 in

FOR MORE
INFORMATION
CLICK HERE 

PROJECT SUPPORT

INSTALLATION GUIDES

WHY NOVA FLEX

RESOURCES