

DESIGN 128 SERIES - IP68

The Nova Flex Design 128 - IP68 is an architectural grade LED ribbon / LED tape lighting that ensures proper execution of design intentions. Ribbon can be installed in both dry and wet locations.



PRODUCT CODE	LUMENS/FT	EFFICACY
NF/SP-DS-W-128-24V-2700K	316	88
NF/SP-DS-W-128-24V-3000K	322	89
NF/SP-DS-W-128-24V-3500K	328	91
NF/SP-DS-W-128-24V-4100K	312	87
NF/SP-DS-W-128-24V-5500K	316	88

Also available in IP65.



Product Shown is Pro 120 - IP68

PHYSICAL

Operating Temp	-15° F to +140° F (-26° C to +60° C)
Class II Max Run	22.9 ft
CRI	90+
Cut Length	2.5 in
Environment	IP68
Mounting	Adhesive / Clips / Channels
Width	0.48 in (12.2 mm)
Height	0.22 in (5.5 mm)



ELECTRICAL

Input Voltage	24V DC
Power Consumption	3.6 w/ft
LEDs/Meter	128
Lamp Life	50,000+ hours
Wire Size	20 AWG, 2 wire
Dimming	MLV / 0-10V
Certifications	UL Listed
Warranty	5 years