

# PRODUCT GUIDE



		DESIGN				H2	PRO			120V	NEON			ADJUSTABLE		
		64	128	160	240	128	60	120	240	FLEX LINE	ROUND	MINI	AQUEOUS	DS 128	DS 160	PRO 120
MAX RUN (ft)	ALL CCT	31.0	22.9	18.0	13.8	13.5	48.8	30.3	15.4	164.0	24.6	49.2	26.2	16.0	13.1	16.4
CUT LENGTH (IN)	ALL CCT	4.92	2.46	1.97	1.31	2.46	3.93	1.96	0.98	7.87	3.28	3.28	2.19	2.46	3.93	3.93
WATTAGE (w/ft)	ALL CCT	2.4	3.6	4.4	6.6	6.7	1.5	3.0	5.9	3.7	3.7	1.4	3.4	1.6 - 3.7	2.1 - 4.5	1.5 - 3.0
LUMENS (lm/ft)	2200K	164	205	272	444	x	x	x	x	x	x	x	x	109 - 272 (2100K-5400K)	138-343 (2100K-5400K)	90 - 184 (3000K-5000K)
	2500K	224	234	326	588	697	x	x	x	x	x	x	x			
	2700K	309	316	424	577	771	94	214	384	309	145	27	153			
	3000K	256	322	397	577	759	115	210	368	307	130	27	164			
	3225K	x	x	x	x	x	103	197	417	x	x	x	x			
	3500K	255	328	407	554	898	x	x	x	333	160	30	x			
	4000K	x	x	x	x	x	x	x	x	325	x	x	x			
	4100K	243	312	411	581	935	101	212	421	x	x	x	x			
	5000K	x	x	x	x	x	x	x	x	337	155	30	x			
	5500K	259	316	384	605	782	92	208	407	x	x	x	x			
	5700K	x	x	x	x	x	x	x	x	x	x	x	151			
	6200K	x	x	x	x	x	87	172	381	x	x	x	x			
	6500K	x	x	x	x	x	x	x	x	334	x	x	x			
EFFICACY (lm/w)	2200K	68	57	62	67	x	x	x	x	x	x	x	x	68 - 74 (2100K-5400K)	65 - 84 (2100K-5400K)	30 - 61 (3000K-5000K)
	2500K	93	65	74	85	104	x	x	x	x	x	x	x			
	2700K	129	88	96	87	115	63	71	65	84	39	19	44			
	3000K	107	89	90	87	113	77	70	62	84	35	19	49			
	3225K	x	x	x	x	x	67	66	71	x	x	x	x			
	3500K	106	91	93	84	134	x	x	x	91	43	22	x			
	4000K	x	x	x	x	x	x	x	x	89	x	x	x			
	4100K	101	87	93	88	140	67	71	71	x	x	x	x			
	5000K	x	x	x	x	x	x	x	x	92	42	22	x			
	5500K	108	88	87	92	117	61	69	69	x	x	x	x			
	5700K	x	x	x	x	x	x	x	x	x	x	x	45			
	6200K	x	x	x	x	x	58	57	65	x	x	x	x			
	6500K	x	x	x	x	x	x	x	x	91	x	x	x			

Stated lumens have a tolerance of +/- 10%.