

DRGB NEON ROUND SERIES

NOVA FLEX[®]

The DRGB Neon Round Series offers architectural-grade LED color changing neon.

- Indoor / Outdoor
- Commercial / Residential
- Accent Direct Lighting



Physical

Operating Temp	-15° to 140°F (-25° to 60°C)
Environment	IP68 Rugged (Water/chemical resistant)
Cut Marks	See diagram below
Mounting	Clips Channel (Required)
Lead Options	Right, Bottom, Left and Right
Bend Radius	4.72 in

Performance

Lumen Maintenance	50,000 Hrs
Warranty	3 years
CCT Binning	<3SDCM
Certifications	UL

Electrical

Voltage	24V
Wire Size	18 AWG. 3 Wire
Dimming	With controller


Dimensions




Right Side Lead Bottom Side Lead Left Side Lead Back Side Lead

ORDER CODE	SERIES	ENV	SHAPE	VOLTAGE	CCT
NF	NEON	W	ROUND	24V	DRGB
NF	NEON	W = IP68	ROUND	24V	DRGB

Neon Ribbon



Lead End & End Cap



CCT	Lumens/ft	Efficacy (lm/w)	Power (w/ft)	Max Run
DRGB	10 - 40	2 - 12	3.7	24.6 ft

Lumens have a tolerance of +/- 10%.

Complete Solution

- Step 1 Build your ribbon order code
- Step 2 Select your channel (pg 2)
- Step 3 Select your power and controls (pg 3-4)
- Step 4 Select your accessories (pg 5)
- Step 5 Contact your local agent or Nova Flex Rep.

DID YOU KNOW?

Product is cut, soldered & shipped ready to install in 1 - 4 business days.

*Special order, allow 4 - 6 weeks delivery.

INSTALL GUIDE

NEON ROUND CHANNEL & CLIPS

NOVA FLEX[®]



Physical

Material	Anodized Aluminum
Length	Custom Length up to 6.56 ft (2M)
Color	Silver


Mounting Options



Direct Mount

POWER SUPPLY OPTIONS DRGB NEON ROUND



ELECTRONIC NON-DIMMING (unless paired with a dimmable controller)

	NF-PS-35W-24V-HW	35W	Input 1.1A Max Output 1.5A / 24V	100 - 240 VAC	UL E345214 Class 2	SPEC SHEET
	NF-PS-60W-24V-HW	60W	Input 1.2A Max Output 2.5A / 24V	100 - 240 VAC	UL E345214 Class 2	SPEC SHEET
	NF-PS-96W-24V	96W	Input 0.96A Max Output 4.1A / 24V	120 - 277 VAC	UL E345214 Class 2	SPEC SHEET
	NF-PS-HLG100W24V-HW	100W	Input 1.2A Max Output 4.0A / 24V	100 - 277 VAC	UL E345214 Class 2	SPEC SHEET









PLUG & PLAY

	NF-PS-12W-24V-WM	12W	0.25A Max	100 - 240 VAC	UL E345214 Class 2	12W SPECS
	NF-PS-24W-24V-WM	24W	0.5A Max			24W SPECS
	NF-PS-36W-24V-TT	36W	0.9A Max	100 - 240 VAC	UL E345214 Class 2	36W SPECS
	NF-PS-60W-24-TT	60W	1.5A Max			60W SPECS
	NF-PS-100W-24V-TT	100W	4.0A Max			100W SPECS

CONTROL OPTIONS DRGB NEON ROUND

Product Image	Product Code	Details	Pair With	Downloads
	LT MINI Dimmer NF-WC-MINI-DRGB	Zones: 1 Receiver Voltage: 12 - 24V DC Receiver Power Capacity: 126W (24V) Remote Voltage: 3V (CR2025) Remote Working Frequency: 433.92 MHz		SPEC SHEET
	LED DMX PIXEL Decoder NF-DMX-PIXELDECODER	Input Signal: DMX512 Input Voltage: 5 - 24VDC Dimming Range: 0 - 100% Operating Temp -22 F to +149 F		SPEC SHEET

ACCESSORY OPTIONS DRGB NEON ROUND

Product Image	Product Code	Dimensions
	Hardwire to Female Quick Connect Adapter NF-C-F	Available Lengths: 6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 8ft & 10ft
	Y Cable 2 Male, 1 Female NF-C-Y	Total Length: 20.00 in
	Hardwire to Male Quick Connect Adapter NF-C-M	Available Lengths: 6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 8ft & 10ft
	Y Cable 4 Male, 1 Female NF-C-Y-4Y	Total Length: 20.00 in
	Male to Female Quick Connect Extension NF-C-MF	Available Lengths: 3ft, 6ft & 10ft
	Y Cable 8 Male, 1 Female NF-C-Y-8Y	Total Length: 17.25 in
	Female Quick Connect to Hardwire Adapter NF-C-F/HW	1.5 x 0.5 x 0.5 in
	Male Quick Connect to Hardwire Adapter NF-C-M/HW	1.5 x 0.5 x 0.5 in

**FOR MORE
INFORMATION
CLICK HERE** 

[PROJECT SUPPORT](#)

[INSTALLATION GUIDES](#)

[WHY NOVA FLEX](#)

[RESOURCES](#)