



SURFACE 4517 CHANNEL

NOVA FLEX[®]



Physical

Material	Anodized Aluminum
Length	2M**
Channel Options [Light Loss]	Silver [10%] Black [20%] White [0%]
Lens Options [Light Transmission]	Clear [92%] Soft [78%] Solid [50%] Black [25%]

Lenses are suitable for outdoor use with respect to exposure to ultraviolet light and water exposure in accordance with UL 746C.

Every 2M of channel comes with 4 mounting clips and two end caps, one with a hole and one solid.

Product Codes for Ordering

Channel	Silver: NF-CH-4517-2M Black: NF/SP-CH-4517-2M-BK* White: NF/SP-CH-4517-2M-WT*
Lens	Clear: NF-CH-4517-C/CLEAR-2M Soft: NF-CH-4517-C/SOFT-2M Solid: NF/SP-CH-4517-C/SOLID-2M* Black: NF/SP-CH-4517-C/BLACK-2M*

Mounting Options




Direct Mount



Adjustable Clip

Angles: 0°/15°/30°/45°/60°/75°/90°
NF-CH-UNV-CLIP/ADJ



Dotting & Compatibility

LEDs	DS64	DS128	DS160	DS240	H2128	PRO60	PRO120	PRO240	ADJ160	RGB60	RGBW60	DRGB48
IP65	1	1	0	0	1	2	1	1	2	2	2	2
IP68	1	1	0	0	0	2	1	0	0	2	2	2

0 - No Dotting



1 - Slight Dotting



2 - Blurred Dotting



3 - Clear Dotting

*Special Order Product Notes:
Lead-time 7-9 weeks
MOQ 150 pcs (2M/pc)

**FOR MORE
INFORMATION
CLICK HERE**



PROJECT SUPPORT

INSTALL GUIDE

WHY NOVA FLEX