

ORDER GUIDE - SIGNATURE SERIES

SS-WHE | WHITE HIGH EFFICIENCY



ORDER CODE BUILDER:

Series	Family	Voltage	Wattage	Environment	Kelvin	Length	Cut Point	Type	Wire In	Wire In Length	Wire Out	Wire Out Length
SS	WHE	24										
			1.0	DRY	22	XX	- Length in inches					
			3.0	DMP	25							
			4.4		27	SFXXX	A	WW	BE	inches	BE	inches
			5.0		30	DFXXX	B	WB	BM		BF	
			6.0		35			WPW	NA		NA	
					40			WG				

Assembly Builder²

EXAMPLE ORDER CODE: SS-WHE-24-1.0-DRY-22-SF90-A-WW-BE-60-BE-5

Notes:

1. Actual values may vary +/- 10%
2. For continuous links consult the factory

ENVIRONMENT

Wire environment will match Linear environment

DRY	IP20
DMP	IP67

WIRE TYPE

Wire environment will match Linear environment

WW	Wire White 20AWG
WB	Wire Black 20AWG
WPW	Wire Plenum White 18AWG
WG	Wire Grey 18AWG

LENGTH - AS AN ASSEMBLY

For continuous links consult the factory

SFXXX



Single Fed - Length in Inches - 3 digits

DFXXX



Double Fed - Length in Inches - 3 digits

WIRE IN

BE



Bare End

BM



Barrel Male

NA



None

CUT POINT

If desired strip length is not possible, should the factory cut above or below your desired length:

B - Below

Cut Below Desired Length

A - Above

Cut Above Desired Length



Desired Cut Length

WIRE OUT

BE



Bare End

BF



Barrel Female

NA



None

IMAGE:



Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Jun.11.25.09:51

800.595.6302

novaflexled.com